

FlexEdge Secure SD-WAN

60 Series

Reliability and security for the distributed enterprise—
introducing FlexEdge Secure SD-WAN 60 Series



Key Benefits

- › The most compact Forcepoint Secure SD-WAN appliances
- › Direct-to-cloud and site-to-site connectivity
- › Simple, robust and cost-effective site solution
- › Centralized management
- › Designed for reliability to help secure business continuity
- › High-availability clustering
- › Best-of-breed security technology with anti-evasion IPS
- › Accelerated inspection of encrypted traffic
- › Built-in anti-virus and anti-bot defenses
- › Access to updates and security policies in just a few clicks
- › Optional URL Filtering powered by Forcepoint ThreatSeeker

Remote offices, branches, and stores can connect directly to the cloud more easily and affordably than ever before. The Forcepoint FlexEdge SD-WAN 60 Series integrates full secure SD-WAN connectivity, advanced high-availability clustering and strong security in a compact, desktop appliance—all managed at enterprise scale from the renowned Forcepoint FlexEdge Secure SD-WAN Manager.

Direct-to-cloud connectivity and security for digital transformation

Digital transformation is all about connecting distributed workforces to the resources they need, no matter where they are, without compromising the security of your infrastructure. With applications and data moving to the cloud, organizations are increasingly finding that old “hub-and-spoke” networking technologies such as MPLS can no longer handle the load.

The Forcepoint FlexEdge SD-WAN 60 series provides the application controls, networking, and security needed to safely connect stores, branches, and remote offices directly to the internet for maximum performance and productivity using the cloud.

Reduced costs and footprint with integrated SD-WAN


The Forcepoint FlexEdge SD-WAN 60 Series unites networking and security in a compact desktop appliance that is easy to install in even the smallest locations. It integrates multi-ISP SD-WAN connectivity, site-to-site Multi-Link™ VPN, and high-availability clustering and intrusion prevention (IPS) security to find, fix, and finish advanced threats before they infiltrate your infrastructure.

You can centrally administer Forcepoint FlexEdge SD-WAN from the same Forcepoint FlexEdge SD-WAN Manager that controls up to 2,000 physical, virtual, and cloud appliances on a single pane of glass. Our Secure SD-WAN Manager allows you to deploy Forcepoint FlexEdge SD-WAN 60 Series devices quickly throughout the world and update them easily, with just a few clicks.

Relentless reliability to help secure business continuity

Downtime is not an option for most organizations. Forcepoint FlexEdge SD-WAN 60 Series offers advanced clustering that groups multiple appliances together (including other Forcepoint FlexEdge SD-WAN models) to keep branch networks running—even in the middle of firmware updates or hardware failure. SD-WAN traffic management lets you use links from more than one ISP at the same time to further reduce the chance of outages. Forcepoint FlexEdge SD-WAN helps you ensure business continuity by keeping your organization connected, despite challenges that may arise.

Forcepoint FlexEdge SD-WAN 60 Appliance



PERFORMANCE ¹	60
Throughput (HTTP 64 KB payload)	350 Mbps
Maximum firewall throughput (UDP 1518 byte)	2 Gbps
Maximum inspection throughput (UDP 1518 byte)	800 Mbps
TLS 1.2 inspection performance (44 KB payload)	110 Mbps
IPsec VPN throughput (AES-GCM-256)	1 Gbps
Concurrent IPsec VPN tunnels	1,000
Mobile VPN clients	Max 25
Maximum inspected concurrent HTTP connections	18,500
Concurrent connections (no inspection)	2,000,000
VLAN tagging	Unlimited

¹ Performance values reflect maximums measured under test conditions and may vary based on configuration and features enabled

ORDERING	60
Forcepoint FlexEdge SD-WAN 60 spare unit	60SPU
Forcepoint FlexEdge SD-WAN Appliance Evaluation	60
URL Filtering	FPURL1X
Advanced Malware Detection	FPAMD1X
60 Series Power Supply Kit	ACP120

PHYSICAL	60
Form factor	Desktop
Dimensions W x H x D	225 x 44 x 150 mm / 8.9 x 1.7 x 5.9 in
Net weight / Appliance + package weight	1.070 kg / 2.145 kg
AC power supply	100-240 VAC 50-60 Hz, 40 W
Typical power consumption	15 W
Max power consumption	21.72 W
Max BTU/Hour	74.06 BTU
MTBF	Minimum 652,732 hours MTBF at 25°C
Operating temperature	0° to ~40° C (32° to ~104°F)
Storage temperature	-20° to ~80° C (-4° to ~176°F)
Relative humidity non-condensing	10% - 90%
Safety certification	CE, CB, UL, LVD, RoHS 3, REACH, FCC, BIS, KCC
EMI certification	FCC Sub Part 47 "B"

NETWORK INTERFACES	N110
Fixed Ethernet interfaces	4 x 1 GbE, RJ45
Wireless	-
Connectors	2 x USB 3.0, Serial Console, DC in 12V